

Lithofin KF Grout Protector

Description

A special product from the LITHOFIN-Range for ceramics, quarry tiles and porcelain (KF). Lithofin KF Grout Protector is a ready-to-use, solvent free special impregnator based on a combination of high quality water and oil repellent compounds.

Technical Data:

Density: approx. 1,0 g/cm³

Appearance: liquid, clear

Odour: unspecified

pH-Value: approx. 4,5

Flash Point: n.a.

Properties

Due to its low viscosity, Lithofin KF Grout Protector penetrates well into porous surfaces. Once dry, the remaining active ingredients show a good water and an excellent oil repellent effect. Oil and other substances remain on the surface where they can easily be removed before they cause stains. Removing greasy kitchen dirt becomes easier. The appearance on the surface is not altered; it may however become slightly darker.

Field of Use

For protecting absorbent, porous cement grouting especially in kitchens and sanitary areas. Absorbent, non-glazed tiles can also be treated.

Directions for Use

The surface to be treated must be absorbent, clean and free of grease. Use Lithofin KF Power-Clean for a deep cleaning of the surface.

Evenly and generously apply Lithofin KF Grout Protector undiluted to the dry surface with a brush or roller. In case of highly absorbent cement grouting, repeat the application several times.

After approx. 20 minutes, carefully remove all surface residues with a cloth. Do not allow the product to dry on the surface.

Please Note: always try the product in an inconspicuous area prior to use. Protect glass, porcelain, polished and varnished surfaces, plastics and other sensitive surfaces against splashes.

Drying Time: approx. 2 hours. The impregnator will be fully effective after 48 hours, protect the surface against water, oil, etc. during this time.

Coverage:

when treating grout joints: approx. 10m² per 500ml.

Storage

Keep closed, cool and dry. Frost-free.

Shelf life of up to two years.

Environmental Protection

Surfactants are biologically degradable in accordance with EU-regulations. Free of solvents. Disposal: containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection systems.

Safety

Contents: polymers; auxiliary agents.

General Information: Keep out of the reach of children. Treated surfaces present no health hazard once dry.

First Aid Procedures: Remove contaminated soaked clothing immediately. In case of inhalation, ensure of fresh air. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). Ensure adequate ventilation. Product does not burn, fire-extinguishing activities according to surrounding.

Additional Information is listed on the Material Safety Data Sheet.

ADR2003: not a dangerous good.

Packaging

500ml bottle with child-proof cap (10 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB11.04gps/11.02)

Agents for Great Britain:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 26 · Fax +44 (0)1962 735 373
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de www.lithofin.com