



## DESCRIPTION

All For Stone™ Enhance'N'Seal™ is a below surface, sealer formulated to provide maximum stain resistance and also enhance and highlight porous unsealed surfaces. Can also be used as a pre-grouting sealer. Allows excellent Moisture Vapour Transmission (MVT) For interior and exterior use.

## USES

UNSEALED Porous Natural Stone, Grout, Concrete, Pavers, etc where an enhanced look and maximum stain resistance is desired

## TEST FIRST

Due to the nature of different surfaces, you should do several tests in inconspicuous areas according to the label instructions to determine application method, number of coats and desired results. The end user must determine the suitability of the product for their intended use.

## PRE-GROUT SEALING

This will allow quick and easy cleanup after grouting as grout may stain surfaces. Do not to saturate the open grout joints. Follow application instructions below.

## PRECAUTIONS

1. Always Test first;
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin and eye protection and use in a well-ventilated area;
4. Surface must be clean and completely dry and free from any other sealers and coatings;
5. Use when surface temperature is between 4°C and 32°C;
6. Once a surface has been enhanced, it cannot be restored to original look.

## INSTRUCTIONS

1. Sweep, vacuum, or wipe surface;
2. Apply product using a sealer Sponge, sealer applicator, paint pad or cotton towels;
3. After 5-10 minutes, remove any sealer visible on the surface by wiping the surface COMPLETELY DRY with absorbent paper or cotton towels. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
4. If 2 or more coats are required, allow minimum 30 minutes between coats (maximum 2 hours) and follow label instructions for each coat;
5. The surface is ready for light traffic after 2 hours. Keep surface dry for 12 hours.

Note: 2 hours after the final coat, conduct a test to determine if the surface is properly sealed by applying a few water droplets to the surface. If the water is easily absorbed then apply an additional coat. Wait 2 hours and repeat the test.

## LIMITATIONS

- Do not allow the product to come in contact with any non-recommended surfaces;
- Regular use of harsh cleaners will affect the performance and enhancement;
- Sealer will not prevent surface wear or etching from harsh chemicals;
- Do NOT apply other sealers, coatings or finishes over Enhance'N'Seal™.

## EXPECTED WEAR

Up to 15 years but will vary depending on texture and hardness of surface, surface wear plus frequency, and type of maintenance products used. Harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners and weather exposure will affect wear and performance. Re-seal as necessary.

## COVERAGE

Approximately 10-40m<sup>2</sup> per 1 litre per coat. The coverage will vary depending on density, porosity, texture, surface absorption, weather conditions, the application method and number of coats.

As a guide: Porcelain Tile 40m<sup>2</sup>, Polished Granite 40m<sup>2</sup>, Sandstone 10-15m<sup>2</sup>, Honed Travertine 18-28m<sup>2</sup>.

## MAINTENANCE

- All For Stone EzyClean™ for routine, everyday cleaning;
- All For Stone XtremeClean™ for periodic heavy duty cleaning;

## HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store and use in temperatures between 4°C and 32°C.

## FIRST AID

For advice, contact a Poisons Information Centre or a doctor. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of accident or if you feel unwell, seek medical advice immediately.

## SAFETY DIRECTIONS

Avoid contact with skin and eyes. May cause stomach distress, nausea or vomiting. May cause respiratory tract irritation. WARNING: KEEP OUT OF REACH OF CHILDREN  
READ SAFETY DIRECTION BEFORE OPENING

## WARRANTY

All For Stone™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

## ALWAYS DO A TEST FIRST.

**All For Stone Limited:** Technical Support  
Phone +44 (0)1244 819939 or Email [technical@allforstone.com](mailto:technical@allforstone.com)  
[www.allforstone.co.uk](http://www.allforstone.co.uk)