

# **Algerase**

# **DESCRIPTION**

United Stonecare Algerase<sup>™</sup> is a highly effective, concentrated product designed to remove green algae, slime, moss and other plant derived deposits. Algerase<sup>™</sup> is self-acting and requires no scrubbing, is easy to use and also prevents re-growth of green algae and "black spot" for up to one year. It does not contain acid or chlorine.

Not suitable for removing "black spot" algae – use Biorase for this.

#### USES

Use on natural stone, concrete flagstones, cement, bricks and wooden surfaces.

#### **TEST FIRST**

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

## **PRECAUTIONS**

- Always test first;
- 2. Read entire label and product technical bulletin before using;
- 3. Wear appropriate skin and eye protection;
- 4. Use when surface temperature is between 10°C and 25°C (do not use on warm surfaces);
- 5. Shield treated surfaces from rain for approximately 4 hours.
- 6. Product is very toxic to aquatic life. Do not allow to contaminate ponds, streams or rivers.

#### **INSTRUCTIONS**

- 1. Remove loose surface dirt with water and a brush;
- 2. Dilute 1:5 with water;
- 3. Best to apply with a garden sprayer on a dry day;
- 4. Thoroughly wet the surface of the stone;
- 5. Keep treated surfaces protected from rain for at least 4 hours.
- 6. Allow 24 to 48 hours for results to begin to show and for algae to
- 7. Rinse with water after several days or simply wait for it to rain.

# **LIMITATIONS**

- For external use only;
- Do not mix with other cleaners or allow product to come in contact with any non-recommended surfaces.
- Contains Quaternary ammonium compounds, benzyl-C12-14 (even-numbered) Alkyldimethyl, chlorides

## **COVERAGE**

Approximately 1 litre of ALGERASE diluted with 5 litres of water will cover approximately 36 square metres.

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method and the severity of the problem.

# **HANDLING AND STORAGE**

- Close container tightly after each use.
- Store in original container only up to 12 months.
- Store in temperatures between 4°C and 32°C.
- Keep off of all other surfaces, clothing and plants.
- Keep out of reach of children and animals.

#### SPILL AGES

Spills of up to 1 litre may be washed into drains with water. Spills of over 1 litre should be absorbed with a suitable absorbent, e.g. sand or sawdust.

#### **FIRST AID**

INHALATION - Remove from exposure. If breathing becomes difficult seek medical attention.

EYE CONTACT - hold eyelids apart and flush the eye continuously with running water for 15 minutes. If worn, remove contact lenses. If irritation persists, seek medical attention.

SKIN CONTACT - remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

INGESTATION – Drink 1 or 2 glasses of water. Do NOT induce vomiting. If irritation or symptoms persist, seek medical attention.

## **SAFETY DIRECTIONS**

Wear protective clothing including overall, gloves and eye protection to prevent skin and eye contact.

#### **WARNING: Corrosive**

R34 Causes severe burns;

S1/2 Keep locked up and out of the reach of children; S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice

S37/39 Wear suitable gloves and eye/face protection S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible) R50 Very toxic to aquatic organisms

#### WARRANTY

United Stonecare™ warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

**ALWAYS DO A TEST FIRST**