

Biorase

DESCRIPTION

United Stonecare BioraseTM is a fast acting and effective cleaner designed to remove black spot algae and green algae. BioraseTM will also treat most organic, coloured food staining such as tea, wine, coffee, cola, iced lollies etc and is suitable for organic staining from birds, berries, leaves, trees, bark, wood, seed, pods and flowers.

LISES

Use on natural stone, wet cast concrete tiles (replica flagstones), pressed concrete tiles, marble, porcelain, ceramic and exterior patios, paths and walls. Biorase[™] will NOT remove cement, grouting, paint, wood preservative stains, oil or mineral type contamination.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

- Always test first;
- 2. Read entire label and product technical bulletin before using;
- 3. Wear appropriate skin and eye protection;
- 4. Use when surface temperature is between 10°C and 25°C;
- 5. Shield treated surfaces from rain for approximately 4 hours.
- 6. Protect plants, textiles, metals, wood etc. as product will damage these surfaces;
- 7. Avoid contaminating ponds, streams and rivers.

INSTRUCTIONS

- Remove everything from the area to be treated and keep product away from all other surfaces;
- Pre-wet the surface if treating during hot, dry conditions. Allow surface water to soak in so there are no puddles. Apply product undiluted and distribute with a brush. Use sufficient to saturate the surface. A garden sprayer can be used to apply product but be careful of overspray or drift;
- 3. Allow to work for 2 to 12 hours depending upon severity. Avoid application when rain is due during the working time;
- Rinse thoroughly after sufficient working time. See www.unitedstonecare.com for information on pressure washing if one is being used;
- 5. Repeat process for areas that are very heavily soiled or where stubborn black spots persist. Rinse well with water and a brush when surface is clean or after a maximum of 24 hours;

LIMITATIONS

- For external use only;
- Do not mix with other cleaners or allow product to come in contact with any non-recommended surfaces.

COVERAGE

Approximately 2 - 5 square metres per litre.

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only up to 12 months.
- Store in temperatures between 4°C and 32°C.
- Keep off of all other surfaces, clothing and plants.
- Keep out of reach of children and animals.

SPILL AGES

Spills of up to 1 litre may be washed into drains with water. Spills of over 1 litre should be absorbed with a suitable absorbent, e.g. sand or sawdust.

FIRST AID

INHALATION - Remove from exposure. If breathing becomes difficult seek medical attention.

EYE CONTACT – rinse cautiously with water for several minutes. If worn, remove contact lenses. If irritation persists, seek medical attention.

SKIN CONTACT - remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

INGESTATION – Rinse mouth. Do NOT induce vomiting. If irritation or symptoms persist, seek medical attention.

SAFETY DIRECTIONS

Wear protective clothing including overall, gloves and eye protection to prevent skin and eye contact.

WARNING: Corrosive

Contains Sodium Hypochlorite

Causes severe skin burns and eye damage;

Contact with acids liberates toxic gas;

Very toxic to aquatic life;

Keep locked up and out of the reach of children;

In case of contact with eyes rinse immediately with plenty of water and seek medical advice

Wear suitable gloves and eye/face protection

In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)

WARRANTY

United Stonecare™ warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST