

ISSUE: 05/01/2015

# TECHNICAL DATA SHEET – HPC 47 NU-CRYL WRS COLOUR ENHANCER

## **DESCRIPTION:**

Nu-Cryl WRS Colour Enhancer is a unique water based modified polysiloxane which provides oil and water repellent properties and lifts the true colour of the substrate.

#### **ADVANTAGES:**

Due to its excellent water repellent qualities, reduces penetration of oil and water, frost damage and organic growth.

Conforms to BS 6477:1992.

Enhances the natural colour of the substrate.

Stain and dirt resistant.

Non-stick and allows easy chewing gum removal.

Will not affect the original colour of the substrate. Highly resistant to weathering and UV exposure. Moisture vapour permeable.

Unaffected by freeze/thaw cycles.

## **USES:**

For use on walls and floors such brickwork, concrete, natural stone, reconstructed stone and blockwork, granite, marble and terrazzo.

#### **COLOUR:**

Milky White. Dries colourless after application.

### **COVERAGE RATE:**

This is dependent upon the porosity of the substrate.

Average coverage rate between 6 - 16m<sup>2</sup>/Ltr

#### **PACK SIZE**

Supplied in 5, 25, 200, 1000 litres.

#### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Hydron SS1 Sterilising Solution.

#### **APPLICATION:**

Shake container well before use. Apply by brush, roller or spray. The surface to be treated should be Impregnated up to saturation point.

One application required. Do not over apply. Remove any excess from the surface after 20 minutes. Do not apply at temperatures below 5°C.

#### **EQUIPMENT CARE:**

All equipment should be cleaned with water immediately after use.

#### **STORAGE:**

Store away from direct sunlight and sources of heat. Protect from frost.

#### **SHELF LIFE:**

12 months (in original sealed container).

## **HEALTH & SAFETY:**

Refer to MSDS.

Unit 7 Phoenix Road Wednesfield Wolverhampton WV11 3PX

TEL: +44(0) 1902 450950





