#### (EN/D)

# **Safety Data Sheet**

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 1 / 8

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Lithofin Rust-EX

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Mixture Washing and cleaning products, aqueous solution

# 1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

**Distributor :** Casdron Enterprises Ltd.

Street : Wood End, Prospect Road

Postal code/city: GB- New Alresford, Hants SO 24 9QF

 Telephone :
 +44 1962 732126

 Telefax :
 +44 1962 735373

 Contact :
 Technical Department E-mail: sales@lithofin.co.uk

Emergency telephone number:

0196 2732126

(Only available during office hours)

**Supplier:** Lithofin AG

Street: Heinrich-Otto-Str. 36
Postal code/city: 73240 Wendlingen
Telephone: +49 (0)7024 9403-0
Telefax: +49 (0)7024 9403-40
Contact: Technical Department
E-mail: info@lithofin.de

Emergency telephone number:

+49 (0)7024 9403-0

(Only available during office hours)

# 1.4 Emergency telephone number

see section 1.3

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4; H302 - Acute toxicity (oral): Category 4; Harmful if swallowed.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

## Additional information

This mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## Remark

Full text of H- and EUH-phrases: see section 16.

## 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

# according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 2/8

sodium mercaptoacetate; CAS No.: 367-51-1

**Hazard statements** 

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

**Precautionary statements** 

P102 Keep out of reach of children.

P270 Do not eat, drink or smoke when using this product.

P280 Wear eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with

local and national regulations.

#### 2.3 Other hazards

#### Adverse human health effects and symptoms

Due to its pH value (see section 9), irritation of the skin and eyes cannot be ruled out.

#### 2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous ingredients**

sodium mercaptoacetate; REACH registration No.: 01-2119968564-24-xxxx; EC No.: 206-696-4; CAS No.: 367-51-1

Weight fraction : ≥ 5 - < 10 %

Classification 1272/2008 [CLP]: Met. Corr. 1; H290 Acute Tox. 3; H301 Acute Tox. 4; H312 Skin Sens. 1; H317

#### **Additional information**

All ingredients of this mixture are (pre)registered according to REACH regulation.

Full text of H- and EUH-phrases: see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

# After ingestion

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

## Self-protection of the first aider

First aider: Pay attention to self-protection!

# 4.2 Most important symptoms and effects, both acute and delayed

No information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Water alcohol resistant foam ABC-powder Carbon dioxide (CO2) Water spray

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 3/8

## Unsuitable extinguishing media

High power water jet Strong water jet

# 5.2 Special hazards arising from the substance or mixture

#### **Hazardous combustion products**

Carbon monoxide Carbon dioxide (CO2)

## 5.3 Advice for firefighters

Use suitable breathing apparatus.

## Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### 5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

## 6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

#### 6.3 Methods and material for containment and cleaning up

## For cleaning up

Suitable material for taking up: Universal binder

#### 6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

#### **Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

# Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

Fire class :

## 7.2 Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Hints on joint storage

Storage class (TRGS 510): 12

Recommended storage temperature 5 - 25 °C

# Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

# 7.3 Specific end use(s)

#### Recommendation

Observe technical data sheet. Observe instructions for use.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

None

# 8.2 Exposure controls

# Personal protection equipment

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 4/8

## Eye/face protection

## Suitable eye protection

Eye glasses with side protection goggles

#### Required properties

**DIN EN 166** 

## Skin protection

## Hand protection

Suitable gloves type: Gloves with long cuffs

Suitable material: NBR (Nitrile rubber), 0,4mm, >8h; Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm,

>8h;

**Recommended glove articles**: Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures: Check leak tightness/impermeability prior to use.

**Remark**: Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

# **Body protection**

Protective clothing.

Suitable protective clothing: Chemical protection clothing Chemical resistant safety shoes

Required properties: alkali-resistant.

Recommended protective clothing articles: DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

Remark: Barrier creams are not substitutes for body protection.

## Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

## Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

#### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

#### General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless
Odour : rotten

# Safety relevant basis data

Freezing point :	( 1013 hPa )	approx.	-3	°C	
Initial boiling point and boiling range :	( 1013 hPa )	approx.	102	°C	
Decomposition temperature : Flash point : Ignition temperature :	( 1013 hPa )		not determined not applicable not determined		closed cup
Sustaining combustion			No		UN Test L2:Sustained combustibility test
Lower explosion limit :			not determined		
Upper explosion limit :			not determined		
Vapour pressure :	(50 °C)	<	3000	hPa	
Density:	(20 °C)	approx.	1	g/cm <sup>3</sup>	Pyknometer
Solvent separation test :	( 20 °C )	<	3	%	
Water solubility	(20 °C)		miscible		
pH:		approx.	9		
log P O/W:			not determined		
Flow time :	(23 °C)	<	15	S	ISO cup 4 mm

# according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 5/8

 Odour threshold :
 not determined

 Vapourisation rate :
 not determined

 VOC-FR
 not applicable

#### 9.2 Other information

None

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No information available.

## 10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

#### 10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

# 10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute effects**

#### Acute oral toxicity

Parameter: LD50 (sodium mercaptoacetate; CAS No.: 367-51-1)

Exposure route : Oral Species : Rat

Effective dose : > 50 - 200 mg/kg
Method : OECD 423

Acute dermal toxicity

Parameter: LD50 (sodium mercaptoacetate; CAS No.: 367-51-1)

Exposure route: Dermal Species: Rat

Effective dose: > 1000 - 2000 mg/kg

Method : OECD 402

# Specific symptoms in animal studies

No data available

## Irritant and corrosive effects

#### Assessment/classification

Causes serious eye damage. Causes severe burns.

# CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

#### Carcinogenicity

No indication of human carcinogenicity.

# Germ cell mutagenicity

# In vivo mutagenicity

#### Other information

No experimental indications of in vivo mutagenicity exist.

# Human toxicological data

## Other information

No indications of human germ cell mutagenicity exist.

#### Reproductive toxicity

## Practical experience/human evidence

No indications of human reproductive toxicity exist.

#### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 6/8

## **SECTION 12: Ecological information**

## 12.1 Toxicity

## **Aquatic toxicity**

#### Acute (short-term) fish toxicity

Parameter: LC50 (sodium mercaptoacetate; CAS No.: 367-51-1)

 Species :
 Fish

 Effective dose :
 > 100 mg/l

 Exposure time :
 96 h

 Method :
 OECD 203

#### Acute (short-term) daphnia toxicity

Parameter: EC50 (sodium mercaptoacetate; CAS No.: 367-51-1)

Species : Daphnia
Effective dose : 38 mg/l
Exposure time : 48 h

#### Acute (short-term) algae toxicity

Parameter: IC50 (sodium mercaptoacetate; CAS No.: 367-51-1)

Species: Algae
Effective dose: 13 mg/l
Exposure time: 72 h
Method: OECD 201

# **Sediment toxicity**

Toxicity to soil macroorganisms

Acute earthworm toxicity

Chronical earthworm toxicity (reproduction)

Long-term toxicity of organisms living in the sediment

## Effects in sewage plants

Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

### 12.2 Persistence and degradability

No data available

#### Abiotic degradation

Abiotic degradation in Water

**Hydrolysis** 

# **Biodegradation**

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No data available

# 12.7 Additional ecotoxicological information

Additional information

The product has not been tested.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Dispose according to legislation.

# Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 7/8

Waste code (91/689/EEC): 16 03 05\*

Waste code packaging

Waste code packaging: 15 01 10\*

#### Waste treatment options

29/35 - Do not empty into drains; dispose of this material and its container in a safe way. Delivery to an approved waste disposal company.

#### Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

#### 13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

## **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

# 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

# 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

## 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

# 14.6 Special precautions for user

None

# **SECTION 15: Regulatory information**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** legislation

REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (clp) Directive 2008/98/EC of the European Parliament and of the Council on waste (2000/532/EC) EN 2:1992 (DIN EN 2:2005-01)

#### Other regulations (EU)

Regulation (EC) No. 648/2004 (Detergents regulation) Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

#### **National regulations**

Observe in addition any national regulations! TRGS 510

## Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to VwVwS

#### Other regulations, restrictions and prohibition regulations

VOCV-Regulation (CH)

Maximum VOC content (Switzerland): < 3 Wt % according to VOCV

# 15.2 Chemical safety assessment

No information available.

#### 15.3 Additional information

# **SECTION 16: Other information**

# 16.1 Indication of changes

03. Hazardous ingredients

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Rust-EX

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 28.06.2017
 Page :
 8/8

# 16.2 Abbreviations and acronyms

None

# 16.3 Key literature references and sources for data

None

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

# 16.5 Relevant H- and EUH-phrases (Number and full text)

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.

# 16.6 Training advice

None

# 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.