

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

Revision date : 30.05.2017  
Print date : 28.06.2017

Version (Revision) : 2.0.0 (1.0.0)  
Page : 1 / 10

**SECTION 1: Identification of the substance/mixture and of the company/ undertaking**

**1.1 Product identifier**

Lithofin KF Tile Restorer

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Mixture Washing and cleaning products, alkaline

**1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)**

**Distributor :**

Casdron Enterprises Ltd.

**Street :**

Wood End, Prospect Road

**Postal code/city :**

GB- New Alresford, Hants SO 24 9QF

**Telephone :**

+44 1962 732126

**Telefax :**

+44 1962 735373

**Contact :**

Technical Department

E-mail: sales@lithofin.co.uk

Emergency telephone number:

0196 2732126

(Only available during office hours)

**Supplier :**

Lithofin AG

**Street :**

Heinrich-Otto-Str. 36

**Postal code/city :**

73240 Wendlingen

**Telephone :**

+49 (0)7024 9403-0

**Telefax :**

+49 (0)7024 9403-40

**Contact :**

Technical Department

E-mail: info@lithofin.de

Emergency telephone number:

+49 (0)7024 9403-0

(Only available during office hours)

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Corr. 1B ; H314 - Skin corrosion/irritation : Category 1B ; Causes severe skin burns and eye damage.

Met. Corr. 1 ; H290 - Corrosive to metals : Category 1 ; May be corrosive to metals.

**Additional information**

This mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Results from in vitro test for skin corrosivity/irritancy: Skin Corr. 1B (OECD 435)

**Remark**

Full text of H- and EUH-phrases: see section 16.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Corrosion (GHS05)

**Signal word**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017  
**Print date :** 28.06.2017

**Version (Revision) :** 2.0.0 (1.0.0)  
**Page :** 2 / 10

Danger

**Hazard components for labelling**

SODIUM HYDROXIDE ; CAS No. : 1310-73-2

**Hazard statements**

H290 May be corrosive to metals.  
H314 Causes severe skin burns and eye damage.

**Precautionary statements**

P102 Keep out of reach of children.  
P234 Keep only in original container.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.

**2.3 Other hazards**

**Adverse human health effects and symptoms**

Due to its pH value (see section 9), irritation of the skin and eyes cannot be ruled out.

**2.4 Additional information**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous ingredients**

SODIUM HYDROXIDE ; REACH registration No. : 01-2119457892-27-xxxx ; EC No. : 215-185-5; CAS No. : 1310-73-2

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318

BUTYL CELLOSOLVE ; REACH registration No. : 01-2119475108-36-xxxx ; EC No. : 203-905-0; CAS No. : 111-76-2

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

sodium etasulfate ; REACH registration No. : 01-2119971586-23-xxxx ; EC No. : 204-812-8; CAS No. : 126-92-1

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315

D-Glucopyranose, oligomeric, C10-16-alkyl glycosides ; REACH registration No. : 01-2119489418-23-xxxx ; EC No. : 600-975-8; CAS No. : 110615-47-9

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315

Potassium cumenesulphonate ; REACH registration No. : 01-2119489427-24-xxxx ; EC No. : 629-764-9; CAS No. : 164524-02-1

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Sodium cumenesulfonate ; REACH registration No. : 01-2119489411-37-xxxx ; EC No. : 239-854-6; CAS No. : 15763-76-5

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Alcohols, C12-15, branched and linear, ethoxylated and propoxylated ; CAS No. : 120313-48-6

Weight fraction :  $\geq 0,5 - < 1$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Aquatic Acute 1 ; H400

**Additional information**

All ingredients of this mixture are (pre)registered according to REACH regulation.

Full text of H- and EUH-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

**Following inhalation**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017

**Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 28.06.2017

**Page :** 3 / 10

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

**In case of skin contact**

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

**After eye contact**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

**After ingestion**

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Water alcohol resistant foam ABC-powder Carbon dioxide (CO<sub>2</sub>) Water spray

**Unsuitable extinguishing media**

High power water jet Strong water jet

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

Carbon monoxide Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

Use suitable breathing apparatus.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

**6.2 Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up**

**For cleaning up**

Suitable material for taking up: Universal binder

**6.4 Reference to other sections**

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017

**Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 28.06.2017

**Page :** 4 / 10

the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

**Fire class :** -

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

#### Hints on joint storage

**Storage class (TRGS 510) :** 8A

**Recommended storage temperature** 5 - 25 °C

#### Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

### 7.3 Specific end use(s)

#### Recommendation

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 20 ppm / 98 mg/m<sup>3</sup>

Peak limitation : 4(II)

Remark : H,Y

Version : 04.11.2017

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts

Limit value : 100 mg/l

Version : 31.03.2004

Limit value type (country of origin) : STEL ( EC )

Limit value : 50 ppm / 246 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )

Limit value : 20 ppm / 98 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

### 8.2 Exposure controls

#### Personal protection equipment

##### Eye/face protection

###### Suitable eye protection

Eye glasses with side protection goggles

###### Required properties

DIN EN 166

##### Skin protection

###### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** NBR (Nitrile rubber), 0,4mm, >8h; Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

Revision date : 30.05.2017  
Print date : 28.06.2017

Version (Revision) : 2.0.0 (1.0.0)  
Page : 5 / 10

## Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** alkali-resistant.

**Recommended protective clothing articles :** DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

**Remark :** Barrier creams are not substitutes for body protection.

## Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

### Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** liquid

**Colour :** yellow

**Odour :** perfumed

### Safety relevant basis data

<b>Freezing point :</b>	( 1013 hPa )	approx.	-11 °C	
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	approx.	97 °C	
<b>Decomposition temperature :</b>	( 1013 hPa )		not determined	
<b>Flash point :</b>		approx.	73 °C	closed cup
<b>Ignition temperature :</b>			not determined	
<b>Sustaining combustion</b>			No	UN Test L2:Sustained combustibility test
<b>Lower explosion limit :</b>			not determined	
<b>Upper explosion limit :</b>			not determined	
<b>Vapour pressure :</b>	( 50 °C )	<	3000 hPa	
<b>Density :</b>	( 20 °C )	approx.	1,1 g/cm <sup>3</sup>	Pyknometer
<b>Solvent separation test :</b>	( 20 °C )	<	3 %	
<b>Water solubility</b>	( 20 °C )		miscible	
<b>pH :</b>		approx.	14	
<b>log P O/W :</b>			not determined	
<b>Flow time :</b>	( 23 °C )	approx.	13 s	ISO cup 4 mm
<b>Odour threshold :</b>			not determined	
<b>Vapourisation rate :</b>			not determined	
<b>VOC-FR</b>			not applicable	

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017  
**Print date :** 28.06.2017

**Version (Revision) :** 2.0.0 (1.0.0)  
**Page :** 6 / 10

### 10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :	LD50 ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )
Exposure route :	Oral
Species :	Rat
Effective dose :	1746 mg/kg
Parameter :	LD50 ( Sodium cumenesulfonate ; CAS No. : 15763-76-5 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 ( sodium etasulfate ; CAS No. : 126-92-1 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg

##### Acute dermal toxicity

Parameter :	LC50 ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )
Exposure route :	Dermal
Species :	Guinea pig
Effective dose :	> 2000 mg/l
Method :	OECD 402
Parameter :	LD50 ( Sodium cumenesulfonate ; CAS No. : 15763-76-5 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg
Parameter :	LD50 ( sodium etasulfate ; CAS No. : 126-92-1 )
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg

##### Acute inhalation toxicity

Parameter :	LC50 ( D-Glucopyranose, oligomeric, C10-16-alkyl glycosides ; CAS No. : 110615-47-9 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 10 mg/l

#### Specific symptoms in animal studies

No data available

#### Irritant and corrosive effects

##### Assessment/classification

Causes serious eye damage. Causes severe burns. Results from in vitro test for skin corrosivity/irritancy: Skin Corr. 1B (OECD 435)

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

##### Carcinogenicity

No indication of human carcinogenicity.

##### Germ cell mutagenicity

##### In vivo mutagenicity

##### Other information

No experimental indications of in vivo mutagenicity exist.

##### Human toxicological data

##### Other information

No indications of human germ cell mutagenicity exist.

##### Reproductive toxicity

##### Practical experience/human evidence

**Trade name :** Lithofin KF Tile Restorer

Revision date : 30.05.2017  
Print date : 28.06.2017

Version (Revision) : 2.0.0 (1.0.0)  
Page : 7 / 10

No indications of human reproductive toxicity exist.

**Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity**

**Acute (short-term) fish toxicity**

Parameter : LC50 ( SODIUM HYDROXIDE ; CAS No. : 1310-73-2 )  
Species : Fish  
Effective dose : 125 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )  
Species : Fish  
Effective dose : 1474 mg/l  
Exposure time : 96 h  
Method : OECD 203  
Parameter : LC50 ( Potassium cumenesulphonate ; CAS No. : 164524-02-1 )  
Species : Fish  
Effective dose : > 100 mg/l  
Exposure time : 96 h  
Method : OECD 203  
Parameter : LC50 ( Sodium cumenesulfonate ; CAS No. : 15763-76-5 )  
Species : Fish  
Effective dose : > 100 mg/l  
Exposure time : 96 h  
Method : OECD 203  
Parameter : LC50 ( sodium etasulfate ; CAS No. : 126-92-1 )  
Species : Fish  
Effective dose : > 100 mg/l  
Exposure time : 96 h

**Chronic (long-term) fish toxicity**

Parameter : NOEC ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )  
Species : Fish  
Effective dose : > 100 mg/l  
Exposure time : 21 d

**Acute (short-term) daphnia toxicity**

Parameter : EC50 ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )  
Species : Daphnia  
Effective dose : 1550 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( Potassium cumenesulphonate ; CAS No. : 164524-02-1 )  
Species : Daphnia  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( Sodium cumenesulfonate ; CAS No. : 15763-76-5 )  
Species : Daphnia  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( sodium etasulfate ; CAS No. : 126-92-1 )  
Species : Daphnia  
Effective dose : > 100 mg/l  
Exposure time : 48 h

**Chronic (long-term) daphnia toxicity**

Parameter : NOEC ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )  
Species : Daphnia  
Effective dose : 100 mg/l  
Exposure time : 21 d

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017  
**Print date :** 28.06.2017

**Version (Revision) :** 2.0.0 (1.0.0)  
**Page :** 8 / 10

Method :	OECD 211
<b>Acute (short-term) algae toxicity</b>	
Parameter :	IC50 ( BUTYL CELLOSOLVE ; CAS No. : 111-76-2 )
Species :	Algae
Effective dose :	1840 mg/l
Exposure time :	72 h
Method :	OECD 201
Parameter :	IC50 ( Potassium cumenesulphonate ; CAS No. : 164524-02-1 )
Species :	Algae
Effective dose :	> 100 mg/l
Exposure time :	72 h
Method :	OECD 201
Parameter :	IC50 ( Sodium cumenesulfonate ; CAS No. : 15763-76-5 )
Species :	Algae
Effective dose :	> 100 mg/l
Exposure time :	72 h
Method :	OECD 201
Parameter :	IC50 ( sodium etasulfate ; CAS No. : 126-92-1 )
Species :	Algae
Effective dose :	> 100 mg/l
Exposure time :	72 h
<b>Bacteria toxicity</b>	
Parameter :	EC50 ( SODIUM HYDROXIDE ; CAS No. : 1310-73-2 )
Species :	Bacteria toxicity
Effective dose :	22 mg/l
Exposure time :	15 min

#### **Sediment toxicity**

**Toxicity to soil macroorganisms**

**Acute earthworm toxicity**

**Chronical earthworm toxicity (reproduction)**

**Long-term toxicity of organisms living in the sediment**

#### **Effects in sewage plants**

Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

#### **12.2 Persistence and degradability**

No data available

##### **Abiotic degradation**

**Abiotic degradation in Water**

**Hydrolysis**

##### **Biodegradation**

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### **12.3 Bioaccumulative potential**

No data available

#### **12.4 Mobility in soil**

No data available

#### **12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **12.6 Other adverse effects**

No data available

#### **12.7 Additional ecotoxicological information**

**Additional information**

The product has not been tested.

### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

Revision date : 30.05.2017  
Print date : 28.06.2017

Version (Revision) : 2.0.0 (1.0.0)  
Page : 9 / 10

Dispose according to legislation.

**Product/Packaging disposal**

**Waste codes/waste designations according to EWC/AVV**

**Waste code product**

Waste code (91/689/EEC) : 06 02 04\*

**Waste code packaging**

Waste code packaging: 15 01 10\*

**Waste treatment options**

29/35 - Do not empty into drains; dispose of this material and its container in a safe way. Delivery to an approved waste disposal company.

**Appropriate disposal / Package**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

**13.2 Additional information**

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

**SECTION 14: Transport information**

**14.1 UN number**

UN 1719

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

CAUSTIC ALKALI LIQUID, N.O.S. ( SODIUM HYDROXIDE )

**Sea transport (IMDG)**

CAUSTIC ALKALI LIQUID, N.O.S. ( SODIUM HYDROXIDE )

**Air transport (ICAO-TI / IATA-DGR)**

CAUSTIC ALKALI LIQUID, N.O.S. ( SODIUM HYDROXIDE )

**14.3 Transport hazard class(es)**

**Land transport (ADR/RID)**

Class(es) : 8  
Classification code : C5  
Hazard identification number (Kemler No.) : 80  
Tunnel restriction code : E  
Special provisions : LQ 11 · E 2  
Hazard label(s) : 8

**Sea transport (IMDG)**

Class(es) : 8  
EmS-No. : F-A / S-B  
Special provisions : LQ 11 · E 2  
Hazard label(s) : 8

**Air transport (ICAO-TI / IATA-DGR)**

Class(es) : 8  
Special provisions : E 2  
Hazard label(s) : 8

**14.4 Packing group**

II

**14.5 Environmental hazards**

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

**14.6 Special precautions for user**

None

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin KF Tile Restorer

**Revision date :** 30.05.2017  
**Print date :** 28.06.2017

**Version (Revision) :** 2.0.0 (1.0.0)  
**Page :** 10 / 10

**EU legislation**

REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (clp)

Directive 2008/98/EC of the European Parliament and of the Council on waste (2000/532/EC)

EN 2:1992 (DIN EN 2:2005-01)

**Other regulations (EU)**

Regulation (EC) No. 648/2004 (Detergents regulation) Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

**National regulations**

Observe in addition any national regulations! TRGS 510

**Water hazard class (WGK)**

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

**Other regulations, restrictions and prohibition regulations**

**VOCV-Regulation (CH)**

Maximum VOC content (Switzerland) : 4 Wt % according to VOCV

**15.2 Chemical safety assessment**

No information available.

**15.3 Additional information**

**SECTION 16: Other information**

**16.1 Indication of changes**

03. Hazardous ingredients

**16.2 Abbreviations and acronyms**

None

**16.3 Key literature references and sources for data**

None

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

No information available.

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

**16.6 Training advice**

None

**16.7 Additional information**

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.