

Lithofin MULTI-SEAL Waterbased Sealant

Description

A special product from the LITHOFIN-Range. This water-based product is ready to use and contains a combination of high-quality natural waxes and additives.

Technical Data:

Density: ca. 1.0 g/cm³

pH-Value: 8-9

Appearance: liquid, whitish

Odour: nearly odourless

Flash point: n.a.

Properties

Lithofin MULTI-SEAL forms a natural satin sheen protective film, which prevents water, dirt and oil from penetrating into the surface making it easier to maintain. Rough surfaces become scuff resistant, smoother and therefore easier to clean. Surfaces maintain their natural colour, the overall appearance is improved through a satin sheen.

Field of Use

For sealing natural stone such as slate, limestone (rough and honed) as well as quarry tiles, concrete stone, concrete slabs and terracotta. Formulated as a finishing treatment after impregnation with Lithofin MN Stain-Stop, Lithofin KF Stain-Stop or any other suitable Lithofin impregnator.

Not suitable for outdoor use.

Directions for Use

The surface to be treated must be clean and completely dry. Apply Lithofin MULTI-SEAL undiluted and spread evenly with a brush, roller or sponge. Two to three coats will generally be needed in order to achieve a uniform appearance. Allow one to two hours drying time between coats

Please Note: Always try the product in an inconspicuous area prior to use. Always treat the entire surface. The surface temperature should be between 5°C and 25°C. Avoid or immediately remove splashes from wood, glass, varnish and other sensitive areas. Do not walk on the surface until it is dry.

Clean application equipment with water.

Drying Time: dry after about 4 hours.

Resilient after about 24 hours.

Completely dry and hard after about 48 hours.

Coverage: approx. 7 to 12m² per litre depending on the surface.

Pre-Treatment

All porous surfaces should be impregnated with the appropriate Lithofin product prior to sealing with Lithofin MULTI-SEAL.

Storage

Keep closed, cool and dry. Frost-free.

Shelf life of up to 2 years. Open containers should be used quickly.

Environmental Protection

The contained surfactants are biologically degradable according to EU-regulations. Does not contain any solvents.

Disposal: containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection systems.

Safety

Keep out of the reach of children. No health concerns once dry.

Ingredients: anionic and non-ionic surfactants; acrylates; waxes; auxiliary agents.

Labelling according to EU-Directive 1272/2008(CLP):

None.

ADR 2015: labelling for transport

Unit	Label	Notes on freight papers
a) b)	--	None

Packaging

- a) 1 litre bottle with child-proof cap (10 per box)
- b) 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB11.15gps/7.16)

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · sales@lithofin.co.uk

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk