

## Lithofin KF Tile Polish

### Description

A special product from the LITHOFIN-Range for ceramic and quarry tiles (KF). The water based acrylate sealant can be diluted with water and is easy to use.

### Properties

Once dry, Lithofin KF Tile Polish forms a film that gives dull, matt and rough surfaces an elegant sheen. Dirt will no longer penetrate into the surface and can easily be wiped away. Rough surfaces become smoother and therefore easier to maintain. The film protects the surface, while at the same time enhancing its appearance by slightly darkening the colours. Existing marks of wear and tear are masked and become less visible.

#### Technical Data:

Density: approx. 1.0 g/cm<sup>3</sup>

pH-Value: approx. 9

Appearance: milky-white

Odour: nearly odourless

### Field of Use

Lithofin KF Tile Polish has been specifically developed for unglazed ceramic surfaces, such as quarry and clay tiles. The surface film enhances the appearance and facilitates maintenance. Lithofin KF Tile Polish is not recommended for outdoor areas or for surfaces subject to heavy wear and tear. Not suitable for glazed and polished tiles.

### Directions for Use

The surface must be clean and completely dried out. Pre-treating the surface with Lithofin KF Stain-Stop is recommended.

Remove dirt deposits and old care product residues with the suitable LITHOFIN cleaner.

Evenly apply Lithofin KF Tile Polish in undiluted form using an applicator, sponge or lint free cloth.

The product may be used diluted with water, if the surface is not very absorbent.

The amount of product to be applied depends on the absorbency of the tile; make sure you leave a clearly visible film of moisture on the surface. A second coat can be applied, if needed. Always test in an inconspicuous area prior to use.

Drying Time: surface will be dry after approx. 40 to 60 minutes, depending on temperature and humidity.

Coverage: approx. 15 to 20m<sup>2</sup> per litre depending on surface.

### Further Care

Occasionally add Lithofin KF Tile Polish to the cleaning water (one cup per ten litres) to touch up and maintain the protective film.

### Storage

Closed and cool, frost free. Shelf life of up to 3 years.

### Environmental Protection

The contained surfactants are biologically degradable according to EU-regulations. Does not contain any phosphates.

Disposal: diluted product may be added to waste water. Containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection system.

### Safety

Keep out of reach of children. No health concerns once dry.

Ingredients: <5% non-ionic surfactants, acrylates, polymers, auxiliary agents.

Labelling according to EU-Directive 1272/2008(CLP):

None

ADR 2015: labelling for transport		
Unit	Label	Notes on freight papers
a) b)	--	none

### Packaging

**a)** 1 litre bottle with child-proof cap (10 per box)

**b)** 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated).

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB8.15gps/--)

### Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · Fax +44 (0)1962 735 373  
 Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de [www.lithofin.co.uk](http://www.lithofin.co.uk)